DT 1990 PRO MKII

Premium Studio Headphone


Order # 1000303 (black)

FEATURES


- Open design
- Rugged spring □eel headband con□ruction
- Circumaural so□ ear pads for high wearing comfo□
- Headband pad with fontanelle recess for pressure relief
- Single-sided detachable mini XLR cable
- Gold-plated mini □ereo jack plug (3.5 mm) & 1/4“ adapter (6.35 mm)
- Made in Germany

SUPPLIED ACCESSORIES

- 1 x “Producing” ear pad set, velours, black, with slight bass boo□, incl. acou□ic disc . . . . . Order # 1001985
- 1 x “Mixing & Ma□ering” ear pad set, velours, black, for linear sound, incl. acou□ic disc . . . . . Order # 1001978
- 1 x PRO X □raight cable, 3 m . . . . . Order # 728471
- 1 x PRO X coiled cable, 5 m (□retched) . . . . . Order # 728489
- 1 x Hard case . . . . . Order # 717967



“Producing”



“Mixing & Ma□ering”

beyerdynamic

beyerdynamic GmbH & Co. KG
Theresien□r. 8 • 74072 Heilbronn / Germany
Tel. +49 (0) 71 31 / 617 - 300 • info@beyerdynamic.com • www.beyerdynamic.com

For fu□her di□ributors worldwide, please go to www.beyerdynamic.com
Non-contractual illu□rations. Contents subject to change without notice. E1/DT 1990 PRO MKII (10.24)

DT 1990 PRO MKII

Premium Studio Headphone

Order # 1000303 (black)

DESCRIPTION

The DT 1990 PRO MKII is an open □udio headphone for mixing, ma□ering and editing. The open design creates a very spatial, dynamic and natural sound with a faithful reproduction of the original.

The e□icient Tesla.45 drivers ensure a pe□ect sound with an excellent resolution, spatiality and high output level.

The DT 1990 PRO MKII features a modern design with a simple elegance of all components such as the end pieces, yokes, ear cups and headband. All components can be replaced and ensure a long life of the headphones.

The single-sided mini XLR cable is detachable and can be locked.

The rugged spring □eel headband gives the headphones a secure fit and the mechanical reliability required for everyday use.

So□ headband and ear pads contribute to a high level of long-term comfo□. Headband and ear pads can be replaced if necessary.

The connection cable is fitted with a gold-plated mini □ereo jack plug (3.5 mm) with a 1/4" adapter (6.35 mm) and can be connected to all □andard headphone outputs.

The delivery includes a hard case for safe transpo□ or □orage.

ACCESSORIES / REPLACEMENT PARTS

Various accessories and replacement pa□s can be found at: **www.beyerdynamic.com**

TECHNICAL SPECIFICATIONS

Transducer type	Dynamic
Operating principle	Open
Wearing type	Circumaural
Frequency response	5 - 40,000 Hz
Nominal impedance	30 Ω
Sound pressure level @ 1 mW/500 Hz	94 dB
Sound pressure level @ 1 V/500 Hz	110 dB
T.H.D. @ 1 mW	0.20% @ 100 Hz 0.06% @ 500 Hz 0.08% @ 1 kHz
Highe□ sho□-term power handling capacity	100 mW
Highe□ nominal power handling capacity (continuous operation)	30 mW
Nominal headband pressure	6 ±0.5 N
Weight (without cable)	376 g
Length and type of cable	3 m / □raight cable or 5 m / coiled cable (□retched), each with 3-pin mini XLR cable connector, detachable, single sided
Connection	Gold-plated mini □ereo jack (3.5 mm) & 1/4" adapter (6.35 mm)

(all specifications acc. to EN 60 268-7)

beyerdynamic

beyerdynamic GmbH & Co. KG
Theresien□r. 8 • 74072 Heilbronn / Germany
Tel. +49 (0) 71 31 / 617 - 300 • info@beyerdynamic.com • www.beyerdynamic.com

For fu□her di□ributors worldwide, please go to www.beyerdynamic.com
Non-contractual illu□rations. Contents subject to change without notice. E1/DT 1990 PRO MKII (10.24)